

100 kW Triton Natural Gas Generator – UL2200 Listed

TP-NG100-S-K-UL



Triton Generators are designed and engineered to power a variety of projects and can be completely customized for your exact requirements.

FEATURES

- ✓ Fully Integrated Power Generation System
- ✓ Prototype-tested, Factory Built and Fully Tested
- ✓ Open-Source Components and Controls
- ✓ Designed to Power any application
- ✓ The Generator set is designed and manufactured in a facility certified to ISO9001:2015, ISO14001:2015, ISO45001-2018 and ISO10002:2014 standards.

OPTIONS:

- Sound Attenuated Enclosure
- Paralleling Controls
- UL2200 and CSA Available
- Extended Warranty
- Trailer with Extended Fuel Capacity
- Over 100 Additional options



OUTPUT RATINGS

Available Voltages At 60Hz	Standby		Prime	
	kW	kVA	kW	kVA
Single Phase, 1.0 Power Factor 110/220, 120/240	75	75	-	-
Three Phase, 0.8 Power Factor 120/240, 120/208, 277/480 *Other voltages available	100	125	-	-

OUR ENGINES

The PSI 5.7LT CAC is a turbocharged, charge-air-cooled industrial natural gas engine engineered to deliver clean, efficient, and reliable performance for modern power generation applications. Operating at 1800 rpm, it produces 122 kWm (163.60 hp), offering strong power output, reduced emissions, and excellent fuel economy. At Triton Power, we choose engines like the PSI 5.7LT CAC because they provide dependable operation, straightforward maintenance, and robust nationwide parts and service support—making them an excellent choice for both prime and standby generator sets where natural gas is the preferred fuel source.

OUR ALTERNATORS

Triton Generators are equipped with Stamford and Leroy-Somer alternators. Utilizing the latest technologies and with outputs extending from 5 to 5,000 kW, these alternators are designed to deliver superior efficiencies in Standby, Continuous and Prime generator applications worldwide.

100 kW Triton Natural Gas Generator – UL2200 Listed TP-NG100-S-K-UL



ENGINE INFORMATION

<i>Engine Make</i>	PSI
<i>Model</i>	5.7LT CAC
<i>Fuel Type</i>	Natural Gas
<i>Engine Speed (RPM)</i>	1800
<i>Engine Power Output at rated RPM (NG)</i>	122 kWm / 163.60 HP
<i>Cooling</i>	Liquid Cooled
<i>Aspiration</i>	Turbocharged, CAC
<i>Total Displacement (Liter)</i>	5.7
<i>No. of Cylinders and Build</i>	6 in line
<i>Bore and Stroke</i>	101.6 x 88.4
<i>Compression Ratio</i>	9.4:1
<i>Governor</i>	Electronic
<i>Fuel Consumption (m3/hr)</i>	
<i>Full Load</i>	35
<i>75% Load</i>	26
<i>50% Load</i>	18
<i>Oil Capacity (Liter)</i>	4.5
<i>Coolant Capacity (Liter)</i>	24.4

ALTERNATOR INFORMATION

<i>Manufacturer</i>	Leroy Somer
<i>Design</i>	Brushless single bearing, revolving field
<i>Stator</i>	2/3 pitch
<i>Rotor</i>	Single bearing, flexible disc
<i>Insulation System</i>	Class H
<i>Standard Temperature Rise</i>	125 -163°C Continuous
<i>Exciter Type</i>	Self Excited
<i>Phase Rotation</i>	A (U), B (V), C (W)
<i>Alternator Cooling</i>	Direct drive centrifugal blower fan
<i>AC Waveform Total Harmonic Distortion</i>	No load < 1.5%. Non distorting balanced linear load < 5%
<i>Telephone Influence Factor (TIF)</i>	<50 per NEMA MG1-22.43
<i>Telephone Harmonic Factor (THF)</i>	<2%

DEEP SEA DIGITAL CONTROLLER

- Adaptable for a wide variety of single gen-set applications, supporting diesel, gas and petrol engines.
- Monitors engine speed, oil pressure, coolant temperature, frequency, voltage, current, power and fuel level, giving you comprehensive engine and alternator protection.
- Easy USB configuration via the DSE PC Suite or directly through the controller's panel.
- Standard units include models DSE4520 or DSE4510. Additional models for AutoStart (DSE73XX and DSE74XX Series) and Synchronization (DSE86XX Series) available upon request on customized equipment.



Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice. All photos are representative and may not reflect exact model

100 kW Triton Natural Gas Generator – UL2200 Listed TP-NG100-S-K-UL



STANDARD ITEMS

- ✓ Engine System:
 - Air Cleaner
 - Commercial Grade Exhaust (Enclosed Versions)
 - Expanded Metal Safety Guards
- ✓ Fuel System
 - Primary Fuel Filter
 - Flexible Fuel Lines
- ✓ Cooling System
 - Factory Installed Radiator
 - Radiator Drain Extension
- ✓ Electrical System
 - Unit Mounted Mainline Circuit Breaker
 - Battery Charging Alternator
 - Battery Tray and Cables
- ✓ Generator Set
 - Mounted on Heavy Duty Steel Base Frame
 - Anti-Vibration Pads between Engine/Alternator and Frame
 - Full Factory Load Bank Testing
- ✓ Alternator
 - Single or Three Phase Available
 - Class H Insulation
- ✓ Enclosure (if selected)
 - Heavy Duty Steel Enclosure (Aluminum Options)
 - Powder Coated Finish
 - Easy Access to All Service Points
 - Fully Sound Attenuated
 - Easy to Transport

OPTIONAL ITEMS

- ✓ Engine System:
 - Upgraded Exhaust Silencers (Hospital, Residential, Critical)
 - Heavy Duty Air filters
 - Oil Drain Extension
 - Oil Heater
 - Block Heater (Standard and Circulating)
- ✓ Fuel System
 - Multi-Valve Fuel Connections
 - Fuel Heater
- ✓ Electrical System
 - Battery Charger (Standard, Float Type and Solar)
 - Additional Circuit Breakers
 - Shunt Trips
 - Electrically Controlled Breakers
 - Remote Emergency Stop Switch
 - Remote Monitoring
 - Paralleling Systems
 - Electrical Connections (Cam-Locks, Reefer Plugs, Distro Panel, and more)
 - Multi Voltage Selector Switches
- ✓ Cooling System
 - Upgraded Radiator Systems
 - Marine Grade Coating
- ✓ Enclosure
 - Aluminum Enclosure
 - Ultra-Quiet Enclosure
 - 20 and 40' Container Packages
 - Custom Paint Colors
 - Rodent Guards
- ✓ Alternator
 - 600 Voltage
 - Medium Voltage
 - Two Bearing
 - Tropicalization
 - Anticondensation Heaters
 - PMG
- ✓ Additional Options
 - Fire Suppression Systems
 - Seismic Isolators
 - Remote Control Systems
 - Enclosure Lights
 - Cold and Extreme Weather Packages
 - NFPA 110 Compliance
 - Standard and Custom Fuel Tanks
 - Standard and Custom Trailers
 - Please inquire, Triton can assist in engineering nearly any option



100 kW Triton Natural Gas Generator – UL2200 Listed TP-NG100-S-K-UL



WEIGHT AND DIMENSIONS


Skid Mounted

Length (mm) in	(2500) 98.4"
Width (mm) in	(1120) 44.1"
Height (mm) in	(1420) 55.9"
Dry Weight (kg) lb	(1,500) 3,306



Enclosed

Length (mm) in	(3665) 144.3"
Width (mm) in	(1178) 46.4"
Height (mm) in	(1910) 75.1"
Dry Weight (kg) lb	(1,950) 4,299



*Drawings are representative only and do not reflect actual product

ENCLOSURE FEATURES AND BENEFITS

- ✓ Made of high-quality steel and completely powder coated. The paint has a three-step process ensuring protection.
- ✓ Advanced water and dust proof design of service doors and enclosure.
- ✓ Noise reduction enhanced by an exhaust silencer and high-quality interior acoustic lining that is sound absorbent and fire-retardant
- ✓ Built for easy installation, maintenance and transport
- ✓ Lifting eyes located at base make it easier to move and transport.
- ✓ Easy to Maintain with Access on both sides, includes Integral base drainage outlets, modular enclosure for easy parts replacement.

TRITON POWER CORP
8511 NW 61 STREET MIAMI, FL USA
305-592-6300 Fax: 305-592-5900
email: info@tritonpower.com
website: tritonpower.com

Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice. All photos are representative and may not reflect exact model